

SAFETY DATA SHEET

1. Identification

Product identifier	NOVAMET 770 AE
Other means of identification	
Article-No.	40777700
Recommended use	Water-miscible metal working fluid. Industrial use.
Recommended restrictions	None known.
Manufacturer/Supplier	Oemeta, Inc. 5655 West 610 South Salt Lake City, UT 84104 Phone: (+1) 801 953-0134 Fax: (+1) 801 953-0446
Further information obtainable from	Oemeta Service Phone: (+49) 4122-924-132 Fax: (+49) 4122-924-157
Emergency Telephone Number	Toll Free Access within USA, Canada, Mexico: 1.866.519.4752 (24h) Outside of the US please call: (+1) 760 476 3962 (24h) Please provide the following code: 333910

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning
Hazard statement	May cause an allergic skin reaction. Causes serious eye irritation.
Precautionary statement	
Prevention	Avoid breathing mist/vapors. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

Supplemental information

4.2% of the mixture consists of component(s) of unknown acute dermal toxicity. Not classified as hazardous according to GHS when diluted to 10% or less.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-(2-butoxyethoxy)ethanol		112-34-5	1 - < 5
Benzotriazole		95-14-7	1 - < 5
Ethanol, 2,2'-(methylimino)bis-		105-59-9	1 - < 5
Sulfonic acids, petroleum, sodium salts		68608-26-4	1 - < 5
Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated		68603-39-4	1 - < 3
ethane-1,2-diol		107-21-1	0.1 - < 1
1,2-Benzisothiazol-3(2H)-one		2634-33-5	0.1 - < 0.5
Other components below reportable levels			80 - < 90

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Hazardous combustion products

Combustion products may include the following: carbon oxides (CO, CO₂); nitrogen oxides (NO, NO₂); sulfur oxides (SO₂, SO₃).

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Recommended storage temperature: between 10 and 30 °C.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-(2-butoxyethoxy)ethanol (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
ethane-1,2-diol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Recommendation: 706 Lapren (KCL, Germany) with a layer thickness of at least 0.6 mm. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Where breathable aerosols/dust are formed, use suitable combination filter for gases/vapours of organic, inorganic, acid inorganic, alkaline compounds and toxic particles (e.g. type A/P2; EN 14387).

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Liquid.
Color	Amber.
Odor	Amine-like.
Odor threshold	Not available.
pH	9 - 10 DIN 51369
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility (water)	Completely miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	960.00 - 990.00 kg/m ³ DIN 51757
Explosive properties	Not explosive.
Kinematic viscosity	45 - 75 mm ² /s DIN EN 16896 (104 °F (40 °C))
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
-------------------	--------------------------------------

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
2-(2-butoxyethoxy)ethanol (CAS 112-34-5)		
<u>Acute</u>		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	2764 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 29 mg/l, 2 hours
Oral		
<i>Liquid</i>		
LD50	Mouse	2410 mg/kg
	Rat	3305 mg/kg
Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated (CAS 68603-39-4)		
<u>Acute</u>		
Oral		
<i>Liquid</i>		
LD50	Rat	> 2000 mg/kg
Benzotriazole (CAS 95-14-7)		
<u>Acute</u>		
Dermal		
<i>Solid</i>		
LD50	Rabbit	> 2000 mg/kg
Oral		
<i>Solid</i>		
LD50	Rat	500 mg/kg
ethane-1,2-diol (CAS 107-21-1)		
<u>Acute</u>		
Dermal		
<i>Liquid</i>		
LD50	Mouse	> 3500 mg/kg
	Rat	> 3500 mg/kg
Inhalation		
<i>Mist</i>		
LC50	Rat	> 5 mg/l, 4 hours 2.5 mg/l, 6 hours
Oral		
<i>Liquid</i>		
LDL0	Human	1600 mg/kg

Components	Species	Test Results
Ethanol, 2,2'-(methylimino)bis- (CAS 105-59-9)		
<u>Acute</u>		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	5990 mg/kg
Oral		
<i>Liquid</i>		
LD50	Rat	4680 mg/kg
Sulfonic acids, petroleum, sodium salts (CAS 68608-26-4)		
<u>Acute</u>		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	> 2000 mg/l
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information		
Ecotoxicity	Not available.	
13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are identified as active on the U.S. EPA TSCA Inventory List.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
ethane-1,2-diol	107-21-1	0.1 - < 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethane-1,2-diol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug Administration (FDA) Not regulated.

US state regulations

US. California Proposition 65

This product can expose you to ethane-1,2-diol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Developmental toxin

ethane-1,2-diol (CAS 107-21-1) Listed: June 19, 2015

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ethane-1,2-diol (CAS 107-21-1)

16. Other information, including date of preparation or last revision

Issue date 06-20-2019

Revision date 02-22-2022
Version # 2.0
HMIS® ratings Health: 1
 Flammability: 1
 Physical hazard: 0

NFPA ratings Health: 1
 Flammability: 1
 Instability: 0

NFPA ratings



Ratings of aqueous dilution HMIS® ratings when diluted to 10% or less: Health: 0, Flammability: 0, Physical Hazard: 0.
 NFPA ratings when diluted to 10% or less: Health: 0, Flammability: 0, Instability: 0.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. The editor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information This document has undergone significant changes and should be reviewed in its entirety.
Approved. TR08032022